VERSION 05/2014

1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier
Trade Name:

VAICO ATF 8HP

VAICO No.:
V60-0264, V60-0265, V60-0267, V60-0268

1.2. Informing department
VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany
Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- Excellent quality properties
- High load capacity, outstanding wear minimisation
- Exceptional friction coefficient consistency
- No foaming
- Very low evaporation loss
- Excellent gear shifting properties at low temperatures
- Adapted friction coefficient properties for sports-style gear shifting
- Outstanding oxidation and thermal stability
- No adverse effect on standard sealing materials

3. USE INSTRUCTIONS

- Specially designed for modern ZF 6-/8- and 9-speed automatic transmissions in high-powered vehicles
- Not for use in DCT/DSG- (Double Clutch) or CVT- (Continuously-Automatic) transmissions suitable.

Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Recommendations*:
Chrysler 68157995AA
BMW L12108 (8322 2 152 426)
Jaguar 02JDE 26444
Land Rover LR 023288
VW / Audi G 060 162 A1/A2/A6 ATF
ZF Lifeguardfluid8 (S671 090 312)

TYPICAL VALUES	METHOD	UNIT	VAICO ATF 8HP
Density at 15°C	*DIN 51 757*	*g/cm3*	*0,846*
Viscosity at 40°C	*DIN ISO 3104*	*mm2/s*	*29,2*
Viscosity at 100°C	*DIN ISO 3104*	*mm2/s*	*6,0*
Viscosity index (VI)	*DIN ISO 2909*	*-*	*158*
COC flash point	*DIN ISO 2592*	*°C*	*>200*
Pour point	*DIN ISO 3016*	*°C*	*-42*
Colour	*-*	*-*	*yellow-green*

* conforms to OEM specifications – The above values may vary within commercially accepted tolerances.