VERSION 11/2016

1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO ATF CVT

VAICO No.:
V60-0117, V60-0211, V60-0212, V60-0213

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany
Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- Extremely high viscosity index
- Excellent wear protection for longest life
- Excellent metal / metal frictional behavior for quiet switching without vibration and outstanding torque transmission
- Unrivalled viscosity-temperature behavior
- Outstanding oxidation and ageing stability
- No adverse effect on standard sealing materials

3. USE INSTRUCTIONS

- Suitable for continuously variable transmission with steel-steel thrust belts or chains.
- Do not mix with other transmission fluids.
- Not suitable for use in hybrid CVT´s (Honda/Ford), DCT/DSG
- (Dual clutch transmissions) or automatic stages.
- Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Approval*:

VW/Audi TL 52 180 (G 052 180)
TL 52 516 (G 052 516)
BMW/Mini EZL799
Chrysler/Dodge/Jeep NS-2/CVTF+4
MB-Freigabe 236.20
Ford WSS-M2C 928-A/CVT23/CVT30
Honda HMMF/HCF2
Mitsubishi CVTF-J1/SP-III
Hyundai/KIA SP-III
Nissan NS-1/NS-2
Suzuki TC/NS-2/CVT Green1
Subaru NS-2/CVTF
Toyota TC

TYPICAL VALUES	METHOD	UNIT	VAICO ATF CVT
Density at 15°C	*DIN 51 757*	*g/cm3*	*0,850*
Viscosity at 40°C	*DIN ISO 3104*	*mm2/s*	*38*
Viscosity at 100°C	*DIN ISO 3104*	*mm2/s*	*7,5*
Viscosity index (VI)	*DIN ISO 2909*	*-*	*181*
COC flash point	*DIN ISO 2592*	*°C*	*210*
Pour point	*DIN ISO 3016*	*°C*	*- 48*

*conforms to OEM specifications – The above values may vary within commercially accepted tolerances