

1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO ATF SPEZIAL

VAICO No.:

V60-0101, V60-0208, V60-0209, V60-0210

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- Extremely high viscosity index
- High load capacity, outstanding wear minimisation
- Low pour point
- No foaming
- High thermal stability
- Reliable friction coefficient characteristic
- Unrivalled viscosity-temperature behaviour
- Excellent oxidation stability
- No adverse effect on standard sealing materials

3. USE INSTRUCTIONS

- Automatic motor vehicle transmissions and torque converters
- Hydrostatic transmissions
- Power steering systems
- Hydraulic systems

Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Recommendations*:

Aisin Warner JWS 3309 · Allison C-4

BMW LT 71141 / 7045E / ETL-8072B / LA2634

Chrysler ATF+3 / ATF +4

Ford FNR5 / Mercon V

GM DEXRON® III G/H · DEXRON® II D/E

Subaru ATF / ATF-HP · Volvo 97340 / 97341

VW G 052 025 / VW G 052 162 / TL 52162

Honda ATF-Z1 · KIA SP-II / SP-III · JASO 1-A

Hyundai SP-II / SP-III · JATCO 3100 PL085

Toyota T-III / T-IV · Nissan Matic D/J/K/S

Mitsubishi Diamond SP-II / SP-III

ZF 02F/ 03D/ 04D/ 05L/ 09/ 11B/ 14A/ 14B/ 16L/ 17C

MAN 339 V1 / V2 / Z1 / Z2

MB approval: 236.1 / 236.2 / 236.5 / 236.6 / 236.7

236.9 / 236.10 / 236.11

Voith H 55.6335.XX (G607) / 55.6336.XX (G1363)

TYPICAL VALUES	METHOD	UNIT	VAICO ATF SPEZIAL
Density at 15°C	DIN 51 757	g/cm ³	0.850
Viscosity at 40°C	DIN ISO 3104	mm ² /s	36
Viscosity at 100°C	DIN ISO 3104	mm ² /s	7.5
Viscosity index (VI)	DIN ISO 2909	-	180
COC flash point	DIN ISO 2592	°C	210
Pour point	DIN ISO 3016	°C	<- 40
Colour	-	-	red