

1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO VA-DOT 4

VAICO No.:

V60-0242, V60-0074, V60-0075, V60-0111

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

2.1. HC-Synthetic fluid.**2.2. High dry and wet boiling point, reducing vapour bubble formation.****2.3. Excellent protection for all metal parts in the brake system against corrosion.****2.4. Good protection against wear and foaming.****2.5. Compatible with all seals and hoses installed in the brake system.**

3. USE INSTRUCTIONS

VAICO VA-DOT 4 is recommended for use in brake and clutch systems in vehicles that require a synthetic DOT 4 brake fluid.
VAICO VA-DOT 4 can be mixed with all synthetic brake fluids of the same grade.

3.1. Special instructions:

3.1.1. Store brake fluid only in sealed original container.

3.1.2. Brake fluid can cause damage to vehicle paintwork.

3.1.3. Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Specifications:

FMVSS 116 DOT 4

SAE J 1703 F

ISO 4925

TYPICAL VALUES	METHOD	UNIT	VAICO VA-DOT 4
Density at 15°C	DIN 51 757	g/cm ³	1.060
Viscosity at -40°C	DIN ISO 3104	mm ² /s	<1350
Dry boiling point (min.)	DIN ISO 4925	°C	>260
Wet boiling point (min.)	DIN ISO 4925	°C	>155