

1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO VA-ZHM

VAICO No.:

V60-0017

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- High viscosity index
- Excellent corrosion protection
- Very low pour point
- No foaming
- Outstanding thermal stability
- Reliable friction coefficient characteristic
- Unrivalled viscosity-temperature behaviour
- Excellent oxidation stability
- No adverse effect on standard sealing materials

3. USE INSTRUCTIONS

- Levelling systems
- Hydro-pneumatic damping systems
- Electro-hydraulic roof controls
- Stabilisation and traction control systems
- Central locking systems

Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Recommendations*:

MB approval 343.0

TYPICAL VALUES	METHOD	UNIT	VAICO VA-ZHM
Density at 15°C	DIN 51 757	g/cm ³	0.865
Viscosity at 40°C	DIN ISO 3104	mm ² /s	16.9
Viscosity at 100°C	DIN ISO 3104	mm ² /s	4.11
Viscosity index (VI)	DIN ISO 2909	-	161
COC flash point	DIN ISO 2592	°C	157
Pour point	DIN ISO 3016	°C	- 45
Colour	-	-	light brown