

1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO SAE 20W-50

VAICO No.:

V60-0010, V60-0011, V60-0198, V60-0024, V60-0199

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

VAICO SAE 20W-50 is a universal SAE 20W-50 mineral engine oil offering excellent protection against wear and corrosion.

3. USE INSTRUCTIONS

VAICO SAE 20W-50 is recommended for use in diesel and petrol engines according to the manufacturer instructions. The SAE 20W-50 classification makes it suitable for year-round use under Central European weather conditions.

4. PERFORMANCE DATA

4.1. Specifications:

API SF/CD

TYPICAL VALUES	METHOD	UNIT	VAICO SAE 20W-50
SAE class	DIN 51 511	-	20W-50
Density at 15°C	DIN 51 757	g/cm ³	0.886
Viscosity at -15°C	DIN 51 377	mPa s	8600
Viscosity at 40°C	DIN 51 562	mm ² /s	154
Viscosity at 100°C	DIN 51 562	mm ² /s	17
COC flash point	DIN ISO 2592	°C	245
Pour point	DIN ISO 3016	°C	- 24
Total base number	DIN ISO 3771	mgKOH/g	6.0

The above values may vary within commercially accepted tolerances