

1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO VA-LHM

VAICO No.:

V60-0112

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- Extremely high viscosity index
- Very low pour point
- Excellent thermal stability
- Outstanding corrosion protection
- No damage to seals

3. USE INSTRUCTIONS

VAICO VA-LHM is a mineral high-performance hydraulic fluid for central hydraulic systems in PSA vehicles with specially labelled green fluid tank. The product exceeds the performance of conventional LHM grades.

Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Recommendations*:

PSA B71 2710 (Citroen/Peugeot)

ISO 7308

TYPICAL VALUES	METHOD	UNIT	VAICO VA-LHM
Density at 15°C	DIN 51 757	g/cm ³	0.845
Viscosity at 40°C	DIN 51 562	mm ² /s	18
Viscosity at 100°C	DIN 51 562	mm ² /s	6,3
Viscosity index (VI)	DIN ISO 2909	-	355
COC flash point	DIN ISO 2592	°C	>100
Pour point	DIN ISO 3016	°C	- 62
Colour	-	-	green fluorescent

* meets the requirements of the OEM manufacturer

The above values may vary within commercially accepted tolerances