

Multispray

Print date: 16.09.2019 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multispray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricant

1.3. VAICO V60-1104

1.4. Details of the supplier of the safety data sheet

Company name: VIEROL AG
Street: Karlstrasse 19

Place: 26123 Oldenburg, Germany

Telephone: +49 (0) 441 – 210 20 - 0 Telefax: +49 (0) 441 – 210 20 - 111

Internet: www.vierol.de

1.5. Emergency telephone +49 (0) 8171 1600-0 during business hours 7am – 5pm (Central European Time,

number: CET)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.





Multispray
Print date: 16.09.2019
Page 2 of 13

P260

Do not breathe spray.



Multispray
Print date: 16.09.2019 Page 3 of 13

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container according to the official regulations.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts. May produce

an allergic reaction.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			50 - <= 100 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220	H280		
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes	, isoalkanes, cyclenes, <2%	aromatics	20 - < 25 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox			
74-98-6	propane	5 - < 10 %		
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220	H280		
106-97-8	butane	1 - < 3 %		
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220			
1471316-72-9	Benzenesulfonic acids, di-C10-14-	alkyl derivatives, calcium sal	ts	< 0.1 %
	939-603-7		01-2119978241-36	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, perfumes.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.



Multispray

Print date: 16.09.2019 Page 4 of 13

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse . In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur . In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours /dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

VAICO_Sicherheitsdatenblatt_Hintergrund



Multispray

Print date: 16.09.2019 Page 5 of 13

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific enduse(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

(CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
	106-97-8	Butane	600	1450		TWA (8 h)	WEL
			750	1810		STEL (15 min)	WEL

VAICO_Sicherheitsdatenblatt_Hintergrund



Multispray

Page 6 of 13

Print date: 16.09.2019 DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
1174921-73- 3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics						
Worker DNEL,	long-term	inhalation	systemic	871 mg/m³			
Worker DNEL,	long-term	dermal	systemic	77 mg/kg bw/day			
Consumer DN	EL, long-term	inhalation	systemic	185 mg/m³			
Consumer DN	EL, long-term	dermal	systemic	46 mg/kg bw/day			
Consumer DNEL, long-term oral systemic 46 mg/kg bw/day							
1471316-72- 9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium	salts					
Worker DNEL,	long-term	inhalation	systemic	35,26 mg/m ³			
Worker DNEL,	long-term	dermal	systemic	25 mg/kg bw/day			
Worker DNEL,	acute	dermal	local	1,04 mg/cm ²			
Consumer DNI	EL, long-term	inhalation	systemic	8,7 mg/m³			
Consumer DN	EL, long-term	dermal	systemic	12,5 mg/kg bw/day			
Consumer DN	EL, acute	dermal	local	0,518 mg/cm ²			
Consumer DN	EL, long-term	oral	systemic	2,5 mg/kg bw/day			

PNEC values

CAS No	Substance			
Environmental	Environmental compartment Value			
1471316-72- 9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts			
Freshwater		0,1 mg/l		
Freshwater (int	ermittent releases)	1 mg/l		
Marine water	Marine water 0,1 mg/l			
Freshwater sed	diment	45211 mg/kg		
Marine sediment 45211 mg/kg		45211 mg/kg		
Micro-organisms in sewage treatment plants (STP)		1000 mg/l		
Soil 36		36739,74 mg/kg		

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long term exposure: after several previous shifts

d before next shift

blood (B)

Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

VAICO_Sicherheitsdatenblatt_Hintergrund



Multispray

Print date: 16.09.2019 Page 7 of 13

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: brown
Odour: sweetish

Test method

pH-Value (at 20 °C): not determined DIN 19268

Changes in the physical state

Melting point: not determined Initial boiling point and boiling range: -42 $^{\circ}$ C Flash point: -80 $^{\circ}$ C

Flammability

Solid: not applicable
Gas: not applicable

Lower explosion limits: 0,6

Upper explosion limits: 9,4

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,783 g/cm³ DIN 51757



Multispray
Print date: 16.09.2019 Page 8 of 13

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / kinematic: < 7 mm²/s

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur . In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.



	Multispray	
Print date: 16.09.2019		Page 9 of 13

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
75-28-5	isobutane					
	inhalation vapour	LC50	1237 mg/l	Mouse.		
1174921-73- 3	Hydrocarbons, C9-C10, n-alkanes, is	soalkanes, c	yclenes, <2% aro	matics		
	oral	LD50 mg/kg	> 15000	Rat	Study report (1977)	
	dermal	LD50	> 5000 mg/kg	Rabbit	Study report (1993)	
	inhalation (4 h) vapour	LC50	> 4951 mg/l	Rat		
106-97-8	butane					
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS	
1471316-72- 9	Benzenesulfonic acids, di-C10-14-al	kyl derivative	es, calcium salts			
	oral	LD50 20000 mg/k	> 10000 - <	Rat	Study report (1972)	
	dermal	LD50	> 2000 mg/kg	Rat	Study report (1989)	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.





Multispray

Print date: 16.09.2019

Page 10 of 13

	T								
CAS No	Chemical name			1	T	T			
	Aquatic toxicity	Dose		[h] [d]	Species	Source			
75-28-5	isobutane				_	_			
	Acute fish toxicity	LC50	91,42 mg/l	96 h	Fish, no other information	United States Environmental Protection A			
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200			
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200			
1174921-73- 3	Hydrocarbons, C9-C10, n-alk	anes, isoalkar	nes, cyclenes, <2%	% aromati	cs				
	Acute fish toxicity	LC50	>1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)				
	Acute algae toxicity	ErC50	>1000 mg/l	72 h	Pseudokirchneriella subcapitata				
	Acute crustacea toxicity	EC50	>1000 mg/l	48 h	Daphnia magna				
	Fish toxicity	NOEC	0,182 mg/l	28 0	Oncorhynchus mykiss	CONCAWE, Brussels Belgium (2010)			
	Crustacea toxicity	NOEC	0,317 mg/l	21 0	Daphnia magna	Company report (2010)			
74-98-6	propane								
	Acute fish toxicity	LC50	49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A			
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200			
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200			
106-97-8	butane	•		•					
	Acute fish toxicity	LC50	49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A			
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200			
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200			
1471316-72- 9	Benzenesulfonic acids, di-C1	0-14-alkyl deri	vatives, calcium s	alts					
	Acute fish toxicity	LC50	> 100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)				
	Acute algae toxicity	ErC50	> 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)			
	Acute crustacea toxicity	EC50	> 1000 mg/l	48 h	Daphnia magna	Study report (1993)			
	Acute bacteria toxicity	(> 10000) mg/l)	3 h	activated sludge of a predominantly domestic sewag	Study report (1994)			



Multispray

Print date: 16.09.2019 Page 11 of 13

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
74-98-6	propane	1,09
106-97-8	butane	1,09
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts	> 6,91

BCF

CAS No	Chemical name	BCF	Species	Source
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics	144,3	calculated	Other company data (
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts	70,8	Fish, not further specified.	Study report (2013)

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2



Multispray
Page 12 of 13

14.4. Packing group:

Hazard label: 2.1 Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

Print date: 16.09.2019

14.1. UN number:UN 1950_14.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:no

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1
14.4. Packing group:

Hazard label: 2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G Passenger LQ: Y203 Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no





Multispray

Print date: 16.09.2019 Page 13 of 13

14.6. Special precautions for user

Warning: Flammable gases.



Multispray

Print date: 16.09.2019 Page 14 of 13

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics; butane

2010/75/EU (VOC): No information available. 2004/42/EC (VOC): No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol directive (75/324/EEC)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H226 Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts. May produce



Multispray

Print date: 16.09.2019 Page 15 of 13

an allergic reaction.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]: Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)